

Cordless Multi tool DTM51



Satisfy Professional's Needs

Tool-less Accessory Change

Lever style lock system allows for quick installation and replacement of the accessories.



Compatible with all OIS accessories (Oscillating Interface System)

Photo: DTM51

Extra Versatility

Wide selection of accessories available for various applications





Cutting PVC, FRP pipes



Wood flush cutting







High operation efficier

- Up to 20,000 oscillations per minute
- 3.2° oscillation angle



Multi angle setting





Fully 360° multi angle setting enables users to position accessories in 12 dif erent angles (each 30°) to allow access to tight spaces for optimum maneuverability.

Items of standard equipment may vary by country or area.

Ergonomically best p

surface of workpiece in variou



- · ergonomically designed to sui required in many dif erent app of accessories.
- · with the on-of slide switch so that you can turn it on/of with holding the grip.



Routing joints on wall tiles











Deep plunge cutting



Battery capacity warning lamp

blade on the s applications.

ossible barrel grip



many diferent ways to grip lications with a wide range

ergonomically positioned the fnger of your hand





BL1850 5.0 Ah



BL1840 4.0 Ah



BL1830 3.0Ah



BL1815/N 1.3/1.5Ah











Cutting plasterboards





Flush cutting of nails



Scraping floor tiles

Wide range of accessories available for various applications

Please see "Accessories for Multi Tool" for detailed information on the shape, size, recommended use and material of each blade.

Cutting (plunge cutting)





Applications:

Cutting of various materials such as oak wood, drywalls, plastics, copper pipes, non-hardened nails, etc.

Benefits:

- Dif erent from jig saws, etc, able to make a plunge cut in the wall for electrical connection box, lighting, exhaust fan, etc.
- The blade can be positioned in twelve dif erent angles to allow easy operation in tight spaces.

Cutting







Applications:

Cutting of various materials such as oak wood, drywalls, plastics, copper pipes, non-hardened nails, etc.

- Able to perform long distance push cut.
- The segment shape allows fush cutting.

Sanding









Applications:

Wood sanding, concrete sanding, or paint removal, etc. with a variety range of abrasive papers

Benefits:

- · Able to sand in corners.
- · Connectable to vacuum cleaner with optional dust extraction system.

Removing grout/ Cutting tiles















Applications:

Replacing broken wall or foor tile.

Benefits:

- · Less amount of dust scattering thanks to oscillating action.
- The segment shape allows f ush cutting.

Scraping









Applications:

Removing mortar, tile adhesive, hardened glue, window putty, caulking, paint, etc.

Benefits:

Low-prof le blade with a narrow tip allows easy removal of caulking, window putty, etc.

Cordless Multi Tool DTM51RFEX5/DTM51Z (Skin Only)

Oscillations per minute (opm) 6.000-20.000

Dimensions (L x W x H) 340x80x122mm (13-3/8"x3-1/8"x4-13/16") with BL1830

Net weight 2.2kg (4.9lbs) with BL1830 or BL1840


Wariable Speed Soft Start





Carrying Case

Standard Equipment: Fast Charger, Battery Cartridge, Oscillating Multi Tool Accessories



Items of standard equipment and specifications may vary by country or area.

