



SIMPLICITY **PANEL LIGHT**

The Long lasting LED panel light is a cost effective solution is an ideal replacement for a traditional fluorescent troffer pack, they can also be surface mounted or hung from the ceiling.

- ✔ 0-10V Dimming
- ✔ High quality LED light source SMD3014, excellent heat dissipation
- ✔ High quality Isolation constant current driver, stable performance, output voltage is DC30-40V
- ✔ High energy saving
- ✔ Environment-friendly, no UV or IR radiation, no heating effect

| CODE | COLOUR TEMP | POWER | LUMENS | DIMENSIONS |
|-----------|-------------|-------|--------|----------------|
| CW-D6060 | 6000K | 36W | 3600 | 595*595*8mm |
| NW-D6060 | 4000K | 36W | 3600 | 595*595*8mm |
| CW-D60120 | 6000K | 50W | 4800 | 1195*595*10mm |
| NW-D60120 | 4000K | 50W | 4800 | 1195*595*10mm |
| CW-P30120 | 6000K | 36W | 4000 | 295*1195*12mm |
| NW-P30120 | 4000K | 36W | 4000 | 295*1195*12mm |
| CW-P60120 | 6000K | 65W | 7000 | 1195*1195*12mm |
| NW-P60120 | 4000K | 65W | 7000 | 1195*1195*12mm |

| SPECIFICATIONS | |
|-----------------------|---------------|
| Lifespan | 50,000 Hours |
| Input Voltage | AC220-240V |
| Beam Angle | 110° |
| Operating Temperature | 20°C~+50°C |
| Certifications | CE, RoHS, SAA |
| Warranty | 3 Years |
| IP Rating | IP44 |
| Frequency | 50Hz |
| CRI | 80 |
| Power Factor | 0.9 |
| LED Type | SMD4014 |
| Diffuser | Frosted |
| Housing Colour | White |
| Dimmable | Yes |