



Main

Device short name	OF SD SDE SDV
Product or component type	Auxiliary contact
Device application	Breaker status monitoring
Range compatibility	Compact NS630b...1600 Compact NS1600b...3200 Compact INS Compact INV Compact NSX EasyPact CVS PowerPact Multistandard Compact NSX DC
Signal contacts composition	1 NO/NC

Complementary

Fault type	General electric fault
Local signalling	ON/OFF indicationopen/close: Trip indicatorrelay trip indicator: Fault tripelectrical fault:
Auxiliary contacts type	Standard
Mounting mode	Clip-on
[I _{th}] conventional free air thermal current	6 A
[I _e] rated operational current	AC-12: 6 A at 24 V AC 50/60 Hz AC-12: 6 A at 48 V AC 50/60 Hz AC-12: 6 A at 110 V AC 50/60 Hz AC-12: 6 A at 220/240 V AC 50/60 Hz AC-12: 6 A at 380/440 V AC 50/60 Hz AC-12: 6 A at 480 V AC 50/60 Hz AC-12: 6 A at 660/690 V AC 50/60 Hz AC-15: 6 A at 24 V AC 50/60 Hz AC-15: 6 A at 48 V AC 50/60 Hz AC-15: 5 A at 110 V AC 50/60 Hz AC-15: 4 A at 220/240 V AC 50/60 Hz AC-15: 2 A at 380/440 V AC 50/60 Hz AC-15: 1.5 A at 480 V AC 50/60 Hz

AC-15: 0.1 A at 660/690 V AC 50/60 Hz
 DC-12: 6 A at 24 V DC
 DC-12: 2.5 A at 48 V DC
 DC-12: 0.6 A at 110 V DC
 DC-12: 0.3 A at 250 V DC
 DC-14: 1 A at 24 V DC
 DC-14: 0.2 A at 48 V DC
 DC-14: 0.05 A at 110 V DC
 DC-14: 0.03 A at 250 V DC

Minimum load	100 mA at 24 V DC
Accessory / separate part category	Spare part for Compact NS630b...1600 Spare part for Compact NS1600b...3200

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------