



Main

Range of product	56 Series™
Product or component type	Rotary switch
Colour tint	Grey
Motor M-rating AS3133	M120
Quantity per set	Set of 4
Type of packing	Carton

Complementary

Number of poles	1
Control type	Rotary
Material	PC (polycarbonate)
Surface finish	Gloss
Installation direction	Vertical
Width	95 mm
Height	95 mm
Depth	62 mm
Rated current	16 A
[Ue] rated operational voltage	240 V
Network frequency	50 Hz
Network number of phases	1 phase
Number of gangs	1 gang
Mounting mode	Surface mounted
Fixing center	84 x 84 mm
Cable cross section	0.75...6 mm ²

Environment

IP degree of protection	IP66
-------------------------	------

Ambient air temperature for operation	-40...55 °C
---------------------------------------	-------------

Packing Units

Package 1 Weight	0.991 kg
Package 1 Height	85.000 mm
Package 1 width	200.000 mm
Package 1 Length	210.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile