TECHNICAL DATA SHEET



INSTRUMENTATION CABLES – MAS SERIES OVERALL SCREEN

MAS5103ES - 1 TRIPLE 1.5MM TCW ES

APPLICATION: Instrumentation Cable suitable Industrial Applications.

Standards AS/NZS1125 , AS/NZS3808 , IEC 60332-1-2 , IEC 60332-3-22 , IEC 60079.14 , <i>RoHS</i> Compliant Conductor Stranded Tinned Copper Conductor
IEC 60079.14 , RoHS Compliant
Conductor Stranded Tinned Copper Conductor
1.5mm (7/0.50mm)
Insulation PVC ,V90HT ,
White/Black/Red Triad
Screen Element Shield of Ali/Polyester Foil c/w
Tinned Copper Drain Wire (7/0.20mm)
Armour Not Applicable
Sheath PVC , 5V-90 , Flame Retardant ,
UV Resistant Black PVC
(Also available in Intrinsically Safe Blue)
Operating Temp. -20°C to +90°C
Rated Voltage 110VRMS/150VDC
Insulation Voltage Rating 300V
Max. Current Rating 13 Amp
Max. DC Resistance @ 20°C 13.6 Ω/km
Max. Capacitance Cond. To 200 pF/m
Cond. (Screened)
Max. Capacitance Cond. To 300 pF/m
Scr. (Screened)
Inductance @ 1kHz 0.95 mH/km
L/R Ratio @ 1kHz 36.5 μH/Ω
Insulation Resistance 140 MΩ/km
Bending Radius (Fixed) 10D (D = Cable Diameter)





Product	Triads	Conductor	Insulation Thickness	Outer Sheath Thickness	Approx. Cable O.D	Approx. Cable Weight
Maser Ordering Code	Number of Triads	mm²	mm	mm	mm	Kg/km
MAS5103ES	1 Triad	1.5mm	0.4	0.8	6.8	76
MAS5103ES BLUE	1 Triad	1.5mm	0.4	0.8	6.8	76

Jacket Marking

MASER MAS5103ES INSTRUMENTATION CABLE 1TR 1.5mm² TCW/PVC/ES/PVC V90 UV ROHS (MANUFACTURE DATE) (METRE MARK)

Disclaimer: Although Maser Communications NZ Limited makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice. Maser provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Maser be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Maser has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

