



Cable Ties

Electrical Connections ICT range of cable ties are designed and manufactured for industry. Injection moulded single piece construction. Manufactured from UL approved, Nylon 6/6, the cable ties are available in both natural and black (UV stabilised). ICT cable ties have advantageous features such as bent tips, easy access ends for fast and secure installation, and a working temp of -40°C - 85°C. ICT cable ties are made to comply with MIL-Spec M-20693B, and the tensile strengths meet or exceed MIL-S 23190.

Light Duty

Part No	Colour	Tensile strength (kg)	Max diameter (mm)	Length (mm)	Width (mm)	Pack Size
ICT10025NC	Natural	8kg	21	100	2.5	100
ICT10025NK	Natural	8kg	21	100	2.5	1000
ICT10025BC	Black	8kg	21	100	2.5	100
ICT10025BK	Black	8kg	21	100	2.5	1000
ICT16025NC	Natural	8kg	40	160	2.5	100
ICT16025NK	Natural	8kg	40	160	2.5	1000
ICT16025BC	Black	8kg	40	160	2.5	100
ICT16025BK	Black	8kg	40	160	2.5	1000
ICT20025NC	Natural	8kg	50	200	2.5	100
ICT20025NK	Natural	8kg	50	200	2.5	1000
ICT20025BC	Black	8kg	50	200	2.5	100
ICT20025BK	Black	8kg	50	200	2.5	1000

Standard Duty

Part No	Colour	Tensile strength (kg)	Max diameter (mm)	Length (mm)	Width (mm)	Pack Size
ICT15033NC	Natural	18	38	150	3.3	100
ICT15033NK	Natural	18	38	150	3.3	1000
ICT15033BC	Black	18	38	150	3.3	100
ICT15033BK	Black	18	38	150	3.3	1000
ICT20036NC	Natural	18	54	200	3.6	100
ICT20036NK	Natural	18	54	200	3.6	1000
ICT20036BC	Black	18	54	200	3.6	100
ICT20036BK	Black	18	54	200	3.6	1000
ICT30036NC	Natural	18	82	290	3.6	100
ICT30036NK	Natural	18	82	290	3.6	1000
ICT30036BC	Black	18	82	290	3.6	100
ICT30036BK	Black	18	82	290	3.6	1000
ICT20048NC	Natural	22	54	200	4.8	100
ICT20048NK	Natural	22	54	200	4.8	1000
ICT20048BC	Black	22	54	200	4.8	100
ICT20048BK	Black	22	54	200	4.8	1000
ICT29048NC	Natural	22	81	288	4.8	100
ICT29048NK	Natural	22	81	288	4.8	1000
ICT29048BC	Black	22	81	288	4.8	100
ICT29048BK	Black	22	81	288	4.8	1000
ICT37048NI	Natural	22	106	370	4.8	50
ICT37048BI	Black	22	106	370	4.8	50
ICT43048NI	Natural	22	115	430	4.8	50
ICT43048BI	Black	22	115	430	4.8	50

• Cable ties for exterior use should be black (UV stabilised).

...continued.



Heavy Duty

Part No	Colour	Tensile strength (kg)	Max diameter (mm)	Length (mm)	Width (mm)	Pack Size
ICT29076NI	Natural	54	82	290	7.6	50
ICT29076BI	Black	54	82	290	7.6	50
ICT37076NI	Natural	54	106	370	7.6	50
ICT37076BI	Black	54	106	370	7.6	50
ICT54076BD	Black	54	160	540	7.6	25
ICT43090ND	Natural	79	115	430	8.8	25
ICT43090BD	Black	79	115	430	8.8	25
ICT77090ND	Natural	79	220	770	8.8	25
ICT77090BD	Black	79	220	770	8.8	25
ICT120090ND	Natural	79	367	1200	8.8	25
ICT120090BD	Black	79	367	1200	8.8	25
ICT153090BD	Black	79	460	1530	8.8	25

Extra Heavy Duty

Part No	Colour	Tensile strength (kg)	Max diameter (mm)	Length (mm)	Width (mm)	Pack Size
ICT30012ND	Natural	114	81	293	12.4	25
ICT30012BD	Black	114	81	293	12.4	25
ICT60012ND	Natural	114	181	618	12.4	25
ICT60012BD	Black	114	181	618	12.4	25
ICT103012ND	Natural	114	312	1030	12.4	25
ICT103012BD	Black	114	312	1030	12.4	25

• Cable ties for exterior use should be black (UV stabilised).



Nylon Cable Tie Mounts

- Material – Nylon 66
- Temperature Range - 40°C to + 80°C
- Flammability – UL 94V-2

Part No	Description	Length (mm)	Width (mm)	Pack Size
CTM19	Adhesive Mount 19x19	19	19	100
CTM28	Adhesive Mount 28x28	28	28	100