



Main

Range	PDL Iconic
Product or component type	Dimmer
Device presentation	Mechanism
Colour tint	Vivid white (VW)
Type of packing	Box
Load type	Incandescent lamp - 300 W Medium voltage halogen lamp - 300 W Low voltage halogen lamp with iron core transformer - 300 W Dimmable fluocompact lamp - 200 W Dimmable LED lighting driver - 200 W Dimmable fluorescent ballast - 200 W
Number of terminals	3

Complementary

Range compatibility	PDL Iconic
Control type	Push-button ControlLink
Fixing mode	Clip-in
Surface finish	Glossy
Ambient air temperature for storage	0...60 °C
Dimmer control	Push type
[Ie] rated operational current	1.2 A
[Ue] rated operational voltage	220...240 V AC 50 Hz 10 W
Function available	Brightness adjustment
Protection type	Short-circuit
Operating distance	30 m
Connections - terminals	Screw terminal
Screwdriver shape	Square drive no 1 (SQ1)

	Philips
Local signalling	LED indicator (warm white)
Material	PC (UL94 V-2): top PC MAS056 (UL94 V-2): bottom
Height	23.5 mm
Width	23.5 mm
Depth	42 mm
Embedding depth	39 mm

Environment

Derating factor	1 deviceswithout derating 2 deviceswith derating factor 3 deviceswith derating factor 4 deviceswith derating factor 5 deviceswith derating factor 6 deviceswith derating factor
Standards	AS/NZS 60669.2.1

Packing Units

Package 1 Weight	50 g
Package 2 Weight	386 g
Package 3 Weight	5.104 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information