Product data sheet Characteristics

PDL387M3T-VW

Switch 300 Series Mechanism - 3-position - Marked ON-OFF-ON - 250 V - 10 A - Vivid White





Main

Range of product	PDL Iconic
Product or component type	Switch
Device presentation	Mechanism
Provided equipment	Switch Rocker dolly
Device application	Lighting
Colour	Vivid white (VW)
Type of packing	Polybag
Quantity per set	Set of 20
Sale per indivisible quantity	1
Load type	Inductive Light Fluorescent lamp

Complementary

Switch function	3 positions	
Control type	Rocker	
Actuator	Rocker	
Fixing mode	Locking bar	
Marking	ON-OFF-ON	
Surface finish	Matt	
Surface treatment	Untreated	
Rated current	10 AX at 250 V AC 50 Hz	
Electrical durability	20000 cycles conforming to AS/NZS 60669	
Connections - terminals	3 screw terminals	
Screwdriver shape	Square drive no 1 (SQ1) Philips No 2	
Clamping connection capacity	1.5 mm² for stranded cable(s) 1.5 mm² for flexible cable(s) 1.5 mm² for rigid cable(s)	
Wire stripping length	10 mm	
Material	PC (polycarbonate): dolly ABS (acrylonitrile butadiene-styrene): dolly	
Height	23 mm	
Width	23 mm	
Depth	50 mm	
Net weight	0.02 kg	

Environment

Ambient air temperature for storage	060 °C
Ambient air temperature for operation	045 °C
Relative humidity	1095 %
Product certifications	RCM

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	