

Product data sheet

Characteristics

PDL384VWP-VW

Iconic - 4gang vert wet hands switch assembly
IP44 10AX 250V vivid white



Main

| | |
|-------------------------------|---|
| Range of product | PDL Iconic |
| Product or component type | Switch |
| Device presentation | Complete switch |
| Provided equipment | Screws Skin IP44 gridplate and switch |
| Device application | Lighting |
| Colour | Vivid white (VW) |
| Type of packing | Polybag |
| Quantity per set | Set of 20 |
| Sale per indivisible quantity | 1 |
| Motor M-rating AS3133 | M80 |
| Load type | Inductive Light Fluorescent lamp |

Complementary

| | |
|------------------------------|--|
| Device mounting | Flush |
| Switch function | 1/2-way |
| Number of gangs | 4 gangs vertical 84 mm |
| Number of rocker | 4 |
| Actuator | Rocker |
| Fixing mode | By screws |
| Surface finish | Matt |
| Surface treatment | Untreated |
| Rated current | 20 A/16 AX at 250 V AC 50 Hz |
| Electrical durability | 20000 cycles conforming to AS/NZS 60669 |
| Connections - terminals | 4 screw terminals |
| Screwdriver shape | Philips No 2 Square drive no 1 (SQ1) |
| Clamping connection capacity | 1.5 mm ² for stranded cable(s) 1.5 mm ² for flexible cable(s) 1.5 mm ² for rigid cable(s) |
| Wire stripping length | 10 mm |
| Material | PC (polycarbonate): skin ABS (acrylonitrile butadiene-styrene): skin PC (polycarbonate): grid plate PP (polypropylene): flaps PC (polycarbonate): housing PA66: housing POM (polyoxymethylene): locking bar TPE (thermoplastic elastomer): switch seal PC (polycarbonate): wall seal |
| Height | 124 mm |
| Width | 82 mm |
| Depth | 40 mm |
| Net weight | 0.098 kg |

Environment

| | |
|---------------------------------------|-----------|
| Ambient air temperature for storage | 0...60 °C |
| Ambient air temperature for operation | 0...45 °C |
| Relative humidity | 10...95 % |
| Product certifications | RCM |
| IP degree of protection | IP44 |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| China RoHS Regulation |  China RoHS Declaration |
| Environmental Disclosure |  Product Environmental Profile |