

Product data sheet Characteristics

PDL681M20FGWH

Switch 600 Series Mechanism - Single-pole -1-gang - Marked OFF-FRIDGE - 250 V - 20 A / 16 AX - White





| Main | | | | |
|---------------------------|------------|--|--|--|
| Range of product | 600 Series | | | |
| Product or component type | Switch | | | |
| Control type | Rocker | | | |

Complementary

| Material | PC (polycarbonate) |
|---------------------------------------|----------------------------|
| Colour tint | White |
| Surface finish | Gloss |
| Installation direction | Horizontal Vertical |
| Length | 23 mm |
| Width | 23 mm |
| Depth | 26 mm |
| Rated current | 16 AX 20 A |
| [Ue] rated operational voltage | 250 V |
| Network type | AC |
| Motor M-rating AS3133 | M60 |
| Network number of phases | 1 phase |
| Number of gangs | 1 gang |
| Number of poles | 1 |
| Mounting mode | Front |
| Ambient air temperature for operation | -1040 °C |
| Cable cross section | 2 x 2.5 mm² 4 x 1.5 mm² |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------|---------------------------------|--|
| REACh Regulation | ☑ REACh Declaration | |
| EU RoHS Directive | Compliant EPEU RoHS Declaration | |
| Mercury free | Yes | |
| RoHS exemption information | ₫Yes | |
| China RoHS Regulation | ☑ China RoHS Declaration | |
| Environmental Disclosure | Product Environmental Profile | |