

Junction Box

Abox-i 025-2,5²



Abox-i 025-2,5²

Junction Box

CUSTOMIZABLE

Productnumber: 49040201

Dimensions: 80 x 80 x 52 mm

Junction box - Industrial Quality - acc. to DIN EN 60670 (VDE 0606), $U_i=690V$, weatherproof, shock-proof, halogen-free, with self-sealing, soft inlet membranes, M20, seal range 2 - 16 mm

Grey, with screw terminal, 5-pole - 2.5 mm² (4 x 1.5² / 4 x 2.5²)



The Spelsberg Abox weather-resistant junction boxes with and without terminals from 1.5 to 240 mm² are extremely impact and break-resistant. They are designed for use in extreme conditions and can be used with a red cover if preferred for identification of safety lighting electric circuits.

Technical Data

electrical characteristics

Protection type UL:	not specified
Rated insulation voltage AC:	690 V
Type of protection:	IP65
Max. conductor cross section:	2,5 mm ²
Protection class:	II

Colours

Base unit colour:	grey
Cover colour:	grey

Dimensions

Width:	80 mm
Length:	80 mm
Height:	52 mm

Material characteristics

suitable for exterior use:	yes
Flammability class according with UL94:	HB
Glow-wire flammability according to EN 60695-2-11:	650 °C
Halogen free:	yes
Industry quality:	yes

mechanical properties

for sealing range max:	16 mm
Type of fastening:	Wall/ceiling mounting
Sealable:	yes
Cover screw torque:	1.7 Nm
for sealing range min:	2 mm
Impact strength:	IK08

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-35 °C
Max. ambient temperature:	80 °C
24h ambient temperature:	60 °C

Material

Base unit material:	ASA-PC
Cover material:	ASA-PC
Sealing material:	Thermoplastic elastomer
Cover screw material:	Stainless steel V2A

Certificates

Test mark:	VDE (DIN EN 60670-1/-22 (VDE 0606-1/-22))
Test mark:	DLG confirmed ammonia resistance in accordance with DLG test directive
Test mark:	DNVGL certified – Class: Shipping & offshore systems

Accessories

[19202001 - KS M20 - Combi set](#)

[22742001 - KVR M20-MGM - Cable gland](#)

[22742101 - KVR M20-GDB/MGM - Cable gland](#)

[23142001 - VST M20 - Sealing plugs](#)

[26012001 - DMS M20/w - Double-membrane seals](#)

[26042001 - DMS M20 - Double-membrane seals](#)

[26202001 - BST M20/sw - Ventilation seal](#)

[26242001 - BST M20 - Ventilation seal](#)

[84000201 - Abox 025/040 KLH-SL 0.2/4² - Clamp mount](#)

[84000401 - Abox 025/040 KLS-2,5²/4² - Terminal block](#)

[89001001 - Abox PST - Sealing kit](#)