

Product data sheet Characteristics

PDL356PB2MBTW-VW

Connected Switch, Iconic, BLE default mode, 2 AX, 240 V, Vivid white





Main	
Range compatibility	PDL Iconic cover plate Pro Series cover plate
Product brand	PDL
Range	Iconic
Product or component	Electronic switch

Complementary

Device presentation	Mechanism	
Load type	Dimmable LED lighting driver: 2 A LED lighting driver (non-dimmable): 2 A Electronic transformer: 2 A Medium voltage halogen lamp: 2 A Linear fluorescent ballast: 2 A Inductive: 2 A (cos phi =0.6) Resistive: 2 A Motor: 2 A	
[Ue] rated operational voltage	220240 V AC 50 Hz	
Protection type	Over temperature protection Thermal protection	
Colour tint	Vivid white (VW)	
Local signalling	LED	
Control type	Push-button By mobile application	
Software name	Wiser by SE App	
Technology type	Bluetooth low energy default Zigbee	
Wiring configuration	3-wire	
Material	Plastic	
Mounting support	Grid	
Device mounting	Flush	
Fixing mode	Clip-in	
Fixing center	84 mm	
Type of installation	Indoor installation	
Embedding depth	40 mm	
Depth	56 mm	
Width	22 mm	
Height	22 mm	

Environment

IP degree of protection	IP20	
Relative humidity	590 % non-condensing	
Standards	AS/NZS 60669.2.1 safety AS/NZS 60669.2.1 EMC AS/NZS 4268 radio	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure		
Circularity Profile	End Of Life Information	